



Assessment of Technologies for the Space Shuttle External Tank Thermal Protection System and Recommendations for Technology Improvement: Part 1 Materi

By Erik S. Weiser

BiblioGov. Paperback. Book Condition: New. This item is printed on demand. Paperback. 26 pages. Dimensions: 9.7in. x 7.4in. x 0.1in. The use of foam insulation on the External Tank (ET) was necessitated by the potentially hazardous build up of ice on the vehicle prior to and during launch. This use of foam was initiated on the Saturn V rocket, which, like the Space Shuttle, used cryogenic fuel. Two major types of foam have been used on the ET. The first type is NCFI 24-124, an acreage material that is automatically sprayed on in a controlled environment. It replaced CPR 488 in 1998 and has been used since that time. The other major foams, BX-250 or BX-265, are handsprayed foams that are used to close out regions where the various sections of the ET are attached. The objectives of the present report are to study the chemistries of the various foam materials and to determine how physical and mechanical anomalies might occur during the spray and curing process. To accomplish these objectives, the report is organized as follows. First, the chemistries of the raw materials will be discussed. This will be followed by a discussion of how chemistry relates to void formation....



[READ ONLINE](#)
[5.77 MB]

Reviews

Good eBook and helpful one. It really is written in straightforward words and phrases and never confusing. I am just effortlessly could possibly get a enjoyment of looking at a published book.

-- Romaine Rippin

The book is great and fantastic. it absolutely was written very properly and beneficial. It is extremely difficult to leave it before concluding, once you begin to read the book.

-- Lyda Davis II